

Archgard

FIREPLACES



25 B-Vent
Insert Fireplace

25 BVI20N

Quality, Design, Dependability

The compact size of the 25 BVI20N B vent gas insert allows for easy installation into factory-built, masonry fireplaces and is specially designed to fit into most B vent fireplace openings. With its range of stylish options, high definition log set, and Archgard's Full Frame Flame, the 25 BVI20N allows you to upgrade your current fireplace to become a stunning, decorative heating appliance and the focal point of your home.

Efficiency

Up to 77% efficient, the 25 BVI20N will provide you with more consistent heat than many existing gas fireplaces. Eliminate the task of providing wood by upgrading to a 25 BVI20N which brings a gas fire that is convenient, clean, and beautiful.

SURROUNDS & DOOR SIZES




3 sided 25-SK3B-2	4 sided 25-SK4B-2
~30 1/4"W X 22 3/4"H	~30 1/4"W X 26 1/2"H
Designer extrusion B	
Black Plate 25-BP *Used behind surround kit if larger surface has to be covered. If wanted, it must be used with one of previous surround kits, cannot be used on its own.	~42"W X 34"H ~4 pieces


TECHNICAL DIMENSIONS

A	B	C	D
24.25"	16.25"	5" to 2"	5"
616mm	413mm	127-51mm	127mm
E	F	G	H
11.25"	15.25"	4"	5.75"
286mm	387mm	102mm	146mm


TOP VIEW




SIDE VIEW



BRICK PANELS



25-BRPL-QCR /
Québec City Red



25-BRPL-QCG /
Québec City Grey

LOUVER KITS

N	Brushed Nickel
G	24k Gold Plated
B	Black

VENTING ACCESORIES

25-ICKIT4 Insert Connector Kit for 4" existing "B" Vent
25-ICKIT5 Insert Connector Kit for 5" existing "B" Vent

For more information, pictures, and videos visit archgard.com

TECHNICAL SPECIFICATIONS

Input Rating	
Natural Gas	15,000-20,000 BTU/hr 4.4-5.8 kW/hr
Propane	16,000-20,000 BTU/hr 4.6-5.8 kW/hr
Efficiencies	
Steady State	77%
Afue Efficiency	71%
P4	49.01%
Clearance to Combustibles	
Minimum fireplace opening	25"/17" W x 15-1/4" H x 12"D
Viewing Area	22"W x 12"H
Vent Size	4" (102 mm)
Mantle Clearance	36" from bottom of unit to bottom of 8" mantle
Side Clearance from face plate	3"

* See the manual for more information.

** All units come standard with barrier screens which attach to the door with very little effort.

ENERGUIDE

Archgard Fireplace Product
7116 Beatty Drive Mission BC V2V 6B4
archgard.com