


## TECHNICAL DIMENSIONS


## TECHNICAL SPECIFICATIONS

Input Rating	
Natural Gas	15,000-20,000 BTU/hr 4.4-5.8 kW/hr
Propane	16,000-20,000 BTU/hr 4.6-5.8 kW/HR
Efficiencies	
Steady State	77%
Afue Efficiency	71%
P4	49.01%
Clearance to Combustibles	
Minimum fireplace opening	25"/17" W x 15-1/4"H x 12"D
Viewing Area	22"W x 12"H
Vent Size	4" (102 mm)
Mantle Clearance	36" from bottom of unit to bottom of 8" mantle
Side Clearance from face plate	3"

TOP VIEW



SIDE VIEW



A	B	C	D
24.25"	16.25"	5" to 2"	5"
616mm	413mm	127-51mm	127mm
E	F	G	H
11.25"	15.25"	4"	5.75"
286mm	387mm	102mm	146mm

### LOUVER KITS

N	Brushed Nickel
G	24k Gold Plated
B	Black

### VENTING ACCESSORIES

- 25-ICKIT4 Insert Connector Kit for 4" existing "B" Vent
- 25-ICKIT5 Insert Connector Kit for 5" existing "B" Vent

\* See the manual for more information.

\*\* All units come standard with barrier screens which attach to the door with very little effort.