

TECHNICAL SPECIFICATIONS


	27 DVIE22N	27 DVIM22N
Valve Type	Electronic Ignition	Millivolt
Natural Gas Input Rating	15,500-22,400 BTU/hr 4.54-6.56 KW/hr	15,500-22,400 BTU/hr 4.54-6.56 KW/hr
Propane Input Rating	16,500-21,000 BTU/hr 4.84-6.15 KW/hr	16,500-21,000 BTU/hr 4.84-6.15 KW/hr
Efficiencies		
Steady State	80%	80%
P4	70.7%	68.3%
Standard Features		
Electronic Ignition	Spark-to-pilot ignition with battery backup and continuous pilot option for standing pilot applications	
Remote Control	Multi-function remote control system c/w smart thermostat	
Convection Fan	High efficiency six speed heat distribution fans	
Glass Type	Ceramic	Ceramic
Viewing Area	22" W x 13-1/2" H - 27" diagonal	22" W x 13-1/2" H - 27" diagonal
Vent Size	Dual 3" (76mm) co-linear vents exit top of unit	Dual 3" (76mm) co-linear vents exit top of unit
Burner Type	Panoramic wall to wall steel pan	Panoramic wall to wall steel pan
Firebox Construction	Welded, rivet and gasket, silicone free	Welded, rivet and gasket, silicone free
Warranty	Elite Limited Lifetime	
Clearance to Combustibles		
Mantle Clearance	33" from bottom of unit to bottom of 12" mantel	33" from bottom of unit to bottom of 12" mantel
Surround Side Clearance	1"	1"
Minimum Fireplace Opening*		
"Controls out": Controls mounted in forward position for deep surround and surround doors	25-1/2" W x 17-3/4" H x 15" D	25-1/2" W x 17-3/4" H x 15" D
"Controls in": Controls mounted for shallow surround or inside fit	30" W x 17-3/4" H x 15-1/2" D	30" W x 17-3/4" H x 15-1/2" D

TECHNICAL DIMENSIONS


CONTROLS OUT CONFIGURATION

CONTROLS IN CONFIGURATION


BOTTOM VIEW




BOTTOM VIEW



FRONT VIEW





FRONT VIEW



27-DVIE22N
27-DVIM33N

A	B
27-1/2"	17-5/8"
697mm	448mm
C	D
15-5/8"	14-1/2"
396mm	406mm
E	G
16-3/4"	38-1/4"
426mm	972mm
H	J
25-3/8"	10-3/8"
644mm	264mm
K	I
15-3/4"	29-7/8"
400mm	759mm

SIDE VIEW



ENERGUIDE

*See Installation, Maintenance, and Operation manual for further information and specifications.

** All inserts come standard with barrier screens which attach to the door with very little effort.